



A WORLD LEADER IN FUME
EXTRACTION TECHNOLOGY

AD Oracle iQ – W3



BOFA Technical Service

If a problem arises with your Oracle iQ system, or if it displays a fault code, please refer to the troubleshooting guide section 8 of this manual. If the problem is still not resolved, please:

- Visit our website at www.bofainternational.com for on-line help.
- Or contact the helpline on **+44 (0) 1202 699 444** Mon-Fri 9am-5pm.
Email: bofatechnical@donaldson.com

Serial Number

For future reference, fill in your iQ system details in the space provided. The serial number is on the rating label located on the side/rear of the unit.

Serial Number:

Contents

1. Overview	4
1.1 IQ Extraction System (Front)	4
1.2 IQ Extraction System (Back)	5
1.3 Overview of LCD Display	6
2. Safety	7
2.1 Safety Notes	7
2.2 Safety Labels	8
3. Before Installation	9
3.1 Unpacking and Unit Placement	9
4. Installation	10
4.1 Fume Capture Methods	10
4.2 Connecting to Power Supply	11
4.3 Optional Added Features	12
4.4 Optional Added Features (contd)	13
5. Operation	14
5.1 Turning Extraction Unit On	14
5.2 Changing the Display Units	14
5.3 Setting the Desired Airflow	15
6. Maintenance	16
6.1 Cleaning the Unit	16
6.2 Replacing Filters	16
6.3 75% Filter Blocked Indication	16
6.4 Pre-Filter Replacement	17
6.5 Combined Filter Replacement	17
7. iQ System Display Features/ Visual Alarms	18
7.1 iQ System Display Features	18
7.2 Visual Alarms on the iQ system	18
7.3 USB Connectivity / USB Upload	21
7.4 Download iQ Data (USB Download)	22
7.5 Information Collected by USB	23
8. Troubleshooting	24
8.1 Fault Indication/Error Codes	24
9. Replacement Parts	25

9.1 Consumable Spares..... 25

9.2 Maintenance Protocol 25

9.3 Filter Disposal 25


9.4 Unit Disposal..... 25

10. System Specifications 26


10.1 Oracle iQ W3 Specifications/Spares 26

1. Overview


1.1 IQ Extraction System (Front)



1.2 IQ Extraction System (Back)



1.3 Overview of LCD Display



2. Safety

2.1 Safety Notes

Important safety notes

Concerning symbols used on the extraction unit and referred to within this manual.



Danger

Refers to an immediate impending danger. If the danger is not avoided, it could result in death or severe (crippling) injury. Please consult the manual when this symbol is displayed.



Warning

Refers to a possible dangerous situation. If not avoided, it could result in death or severe injury. Please consult the manual when this symbol is displayed.



Caution

Refers to a possible harmful situation. If not avoided, damage could be caused to the product or something in its environment.



Important (Refer to manual)

Refers to handling tip and other particularly useful information. This does not signify a dangerous or harmful situation. Refer to manual when this symbol is displayed.

EU Declaration

The unit has been designed to meet the essential Health and Safety requirements of the Machinery Directive 2006/42/EC, Low Voltage Directive 2014/35/EC and the EMC Directive 2014/30/EU. For the full DOC and further information please contact the technical team at www.bofainternational.com.

Electrical Safety

The unit has been designed to meet the essential Health and Safety requirements of the Low Voltage Directive 2014/35/EC. The requirements of the EMC Directive 2014/30/EU are also met.

Warning

When working with the pump/motor housing open, Live 230/115 volt mains components are accessible. Ensure that

the rules and regulations for work on live components are always observed.

Important

To reduce the risk of fire, electric shock or injury:

1. Always isolate the system from the mains power supply before removing the pump/motor access panel.
2. Use only as described in this manual.
3. Connect the system to a properly grounded outlet.

Dangers to eyes, breathing and skin

Once used, the filters within the Oracle iQ system may contain a mixture of particulates, some of which may be sub-micron size. When the used filters are moved it may agitate some of this particulate, which could get into the breathing zone and eyes of the operative. Additionally, depending on the materials being processed, the particulate may be an irritant to the skin.

Caution: When changing used filters always wear a mask, safety shoes, goggles and gloves.

Carbon selection

Please note that the media within the gas filter fitted in the Oracle iQ is capable of adsorbing a wide range of organic compounds. However, it is the responsibility of the user to ensure it is suitable for the particular application it is being used on.

Intended use

This equipment has been designed to extract and filter fume from a variety of applications. However, it is the users responsibility to ensure the equipment is installed correctly and is suitable for the application.

This machine must not be used on wet applications or acidic fumes. When using the machine never mix ferrous and non ferrous metals.

Do not filter titanium.

2.2 Safety Labels

Warning and Information labels

The following listing details labels used on your Oracle iQ unit.

Goggles, Gloves & Mask Label



Meaning: Goggles, Gloves and Masks should be worn while handling used filters.



Do Not Cover Label



Meaning: Do not cover any louvers or holes adjacent to the label.

Electrical Danger

Meaning: Removal of panels with this label attached will allow access to potentially live components.


Warning Label



Meaning: Power should be isolated before the panel with this label attached is opened/ removed.

W3 filter label

Label for welding fume separation equipment as per ISO 15012-1.



Serial Number Label



Meaning: This label contains a variety of information about the extraction unit, including.

- Company name, Address & Contact number
- Extractor model
- Unit serial number
- Operating voltage range
- Maximum current load
- Operating frequency
- Year of Manufacture
- Relevant approval markings/ logos

PLEASE NOTE: If the equipment is used in a manner not specified by the manufacturer, the protection provided by the equipment may be compromised.

Fire Risk Warning

In the very rare event that a burning ember or spark is drawn into the fume extraction unit, it may be possible that the filters will ignite.

Whilst any resultant fire would typically be retained within the fume extraction unit, the damage to the extractor could be significant. It is therefore essential to minimise the possibility of this occurring by undertaking an appropriate risk assessment to determine:

- a). Whether additional fire protection equipment should be installed.
- b). Appropriate maintenance procedures to prevent the risk of build-up of debris which could potentially combust.

W3 certification is usually employed to mitigate the risk of fire in several applications, including welding applications. However, BOFA do not recommend the use of our extractors in welding-only processes (irrespective of the W3 compliance) and for other applications which may involve the regular or vigorous generation of sparks. In these circumstances, the additional spark arrestor 2 product should be used.

3. Before Installation

3.1 Unpacking and Unit Placement

Inner transit packaging removal & unit placement

Before installation, check the extraction unit for damage. All packaging must be removed before the unit is connected to the power supply.

Please read all instructions in this manual before using this extractor.

1. Move the unit to the location where it is going to be installed and remove the outer packaging. **This unit should be installed in a well-ventilated area.**
2. Open the front door and remove the transit foam from the centre of the unit.




Caution

Due to the weight of the extractor suitable lifting equipment should be used and with regard to appropriate safety precautions. (See Appendix for product weight details).

Ensure that 500 mm space is available around any vented panels on the extractor to ensure adequate airflow.

3. With the unit in position lock the 2 front castors.



Caution

Do not block or cover the cooling vents on the unit, as this severely restricts airflow and may cause damage to the unit.



Caution

Under no circumstances should the exhaust outlet/s be covered as this will restrict the airflow and cause overheating.

4. Check the filters are located in their correct position before closing the door and securing the door latches.

Note: The unit will not operate correctly if the Combined filter has not been secured in place using the internal lever. (As detailed below)



4. Installation

The Oracle iQ has been designed to remove and filter fume containing potentially hazardous particulate and gases generated during manufacturing processes. Such hazardous substances are captured within a multistage filtration system after which the cleaned air is returned to the workplace.

4.1 Fume Capture Methods

The fume is normally captured by 1 of 3 methods.

- **Flexible arm/ Nozzle**
- **Enclosures**
- **Cabinets**

General Guidelines for a successful installation

- Keep duct run length to a minimum
- Avoid sharp bends / turns in the ductwork
- Avoid multiple bends / turns in the ductwork
- Use a larger diameter duct where able
- Position the capture device as close as possible to the marking point. (If used on high speed lines, position the capture device slightly downstream)


Flexible Arm & Nozzle Extraction

The stay put arm should be mounted as close as possible to the marking point using the horseshoe clips. Unscrew the push fit connector from the other side of the flexible hose. Cut the flexible hose to suit the distance back to the extractor connection and push onto the extractor inlet.

Purge air should be kept to a minimum, where possible, to prevent the fume being blown away from the nozzle. High speed production lines may need bigger scoops or nozzles both sides of the bottles because of the turbulence caused by the speed of the bottles.


Moving products

For applications where the product to be marked is moving past the stationary laser head the capture nozzle should be positioned as close as possible to the marking area on the side the product is moving towards.




Enclosures

The extraction hose and nozzle can be attached to the enclosure surrounding the marking zone provided that the extraction point is within 50-75mm of the marking point.



Cabinets

Cabinets normally have a 75mm or 100mm spigot for fume extraction. For best performance use the same diameter hose as the spigot and reduce at the extractor end if necessary. **Keep the hose run as short as possible.**



Connection to extraction unit

All ductwork should be installed and connected to the extraction unit before the iQ system is turned on.

Exhausting filtered air outside

If requested your iQ extraction unit will have been fitted with an exhaust outlet spigot. This provides a connection point for exhaust pipework to be fitted. It is important to keep any ducting to a minimum, in order to reduce back pressure within the system.

Specification

Refer to section 10.1.

4.2 Connecting to Power Supply

Please follow the above specification when selecting the power supply outlet for the iQ system, ensure the power supply is suitable before connecting the iQ system.

Check the Integrity of the electrical power cable, if the supply cord is damaged the extraction unit should not be connected to the mains. The supply cord should only be replaced by a BOFA engineer as an electrical safety test may be required after replacement.

This extractor is not supplied with power cord included. If you require one, please use the part numbers below:

- 1UA1070572 – UK power cord
- 1UA1070573 – EU power cord



The iQ system **MUST** be connected to a properly earthed outlet.

If your iQ system was ordered with any optional extras please read section 4.3 before the power connection is made as additional connections may be required before power is connected to the extractor.



Connect the power cable to an isolated electrical supply.

The mains socket should be installed near the extractor; it should be easily accessible and able to be switched On/ Off. The cable run should be arranged so as not to create a trip hazard.

4.3 Optional Added Features

Interface features

The iQ Oracle can be configured to suit customer specification. These optional extras would be discussed, arranged and installed prior to delivery.

(If unsure what features your iQ system is equipped with please contact the seller with the unit serial number, (Refer to section 2 for location) who will be able to advise what specification has been supplied.

Remote Stop/Start feature

Enables the extraction unit to be remotely turned On / Off via an external signal.

This feature can be configured in 3 ways

- DC Voltage input – Range 12-24VDC
- Volt free input – Open / Closed contacts
- Override – Stop / Start feature switched off

Note: Care must be taken to ensure that the system is correctly wired in order for the extraction unit to function correctly.

DC Voltage input

This configuration requires the Black & Red cores of the signal cable (Refer to section 1 for location) to be connected to a known and tested DC power supply, in order to start the extractor.

The operating voltage for this signal is between 12 & 24VDC. Only voltages within this range should be connected. Voltages connected outside of this range may cause irreversible damage to the internal control PCB.

Red cable = V+

Black cable = V-

When the extractor is provided with the correct DC voltage the motor will start and maintain the set flow rate (Refer to section 5 for how to set the flow) when the DC voltage is removed the motor will slow down and come to a stop.

The extractor will need to be turned on and be out of standby mode (See section 5 for turning the extractor on) in order for this feature to operate.

Volt free input

This configuration requires the Black & Red cores of the signal cable (see section 1 for location) to be connected together, in order to start the extractor.

When the 2 cables are connected together the motor will start and maintain the set flow rate (see section 5 for how to set the flow)

when the 2 cables are disconnected the motor will slow down and come to a stop.

The extractor will need to be turned on and be out of standby mode (See section 5 for turning the extractor on) in order for this feature to operate.

Override

Enables the extractor to operate fully with or without either DC voltage input or the Volt free input.


The override feature can be toggled On / Off by a switch mounted on the internal motor access panel (see below for switch location)

Switch in "On" position

In this position the extractor will require a start signal (either Voltage input or Volt free, depending on the requested specification) to enable the motor within the extraction unit.

Switch in "Off" position

In this position the extractor motor will run without the requirement for an external start signal. This feature is useful for engineers carrying out works/ tests on the extractor without the need for the laser / auxiliary signal being present.



4.4 Optional Added Features (contd)

Filter Blocked / System Fail Signal

With this option the iQ system will output a signal to alert the user when the extractor has failed or when the filters are blocked.

This feature will not directly stop the extractor from running correctly, but if fitted this feature should be terminated correctly before power is applied to the iQ system.

Connection specification

This signal is available via the Green and White cores of the signal cable. The iQ system will provide a volt free Open / Closed signal that can be connected to an external interface, beacon or warning device following the specification below.

- **Maximum input voltage: 24V AC**
- **Maximum current load: 3A @ AC**
OR
- **Maximum input voltage: 24V DC**
- **Maximum input load: 3A @ DC**

Filter Signal Configurations

There are 3 ways this signal can be configured, as detailed below.

- **Combined signal (standard specification)**
- **Separated signal**
- **Reversed separated signal**

Combined signal configuration

With this configuration the Filter blocked & System fail signals will be linked together to give a combined single output.

When the filters become blocked or the iQ system develops a fault (Refer to section 8 for Troubleshooting & Error codes) the connection between the Green & White cables will become "Open"

When the extraction system is running normally the connection between the Green & White cables will become "Closed"

Separated Signal

With this configuration the Filter blocked & System fail signals will be separated to give 2 individual signals.

When the filters become blocked the connection between the Green & White cables will become "Open"

If the iQ system develops a fault (Refer to section 8 for Troubleshooting & Error codes) the connection between the Blue & Yellow cables will become "Open"

When the extraction system is running normally the connection between the (Green / White) & (Blue / Yellow) cables will become "Closed"

Reversed Separated Signal


With this configuration the cable function will remain the same as the **Separated signal** option, but the signal given will be reversed.

For blocked filters the connection between the cable cores will be "Closed"


For iQ system faults the connection between the cable cores will be "Closed"

For system OK the connection between the cable cores will be "Open"

Combined Signal



Separated Signal




Compressor option

If a compressor has been fitted to the extraction unit, connect the compressor hose, to the extractor compressor outlet (Refer to section 1 for location) and connect the opposite end to the laser. Refer to laser installation instructions. A water trap should be fitted to the Laser end of the pipework.

5. Operation

5.1 Turning Extraction Unit On

There are two stages to powering up your iQ extraction unit. Firstly, the main isolation switch must be switched to the "On" position (Refer to section 1 for switch location) by depressing the Green side / (I) of the switch. This will place the extraction unit in Standby mode, indicated by the front panel power button glowing red.




Stainless Steel

To start the extraction unit, press the front panel power button (refer to section 1 for switch location) the button will change from Red to Green indicating the extraction unit is now fully On.

It is recommended that the rear isolation switch is left in the On position and the front standby switch is used to toggle the extractor On / Off.

Standby



On




5.2 Changing the Display Units

The Airflow and temperature readings can be displayed in two ways.


1. **Temperature displayed as °C**
Airflow displayed as m³/h
OR
2. **Temperature displayed as °F**
Airflow displayed as CFM

The display value can be changed by pressing the "Enter" button once.

1)



2)



5.3 Setting the Desired Airflow

The iQ system features automatic flow control. This enables the user to set the required airflow rate, then over time as the filters begin to block the motor will automatically begin to increase in speed to compensate for any loss in performance caused by the added restriction of the partially blocked filters.



The extractor and all pipe work must be fully installed and connected before the airflow is set.

To set the airflow

(The airflow can be set between 100-370m³/h)

1. Press and hold the "Enter" (middle) button (Refer to section 1 for button location) for three seconds, or until all three button lights flash green.
2. Release the "Enter" button, the iQ system is now in set mode. Press either the Up or Down button to adjust the airflow accordingly. Real time airflow is displayed on the LCD screen, Refer to section 1 for Display information).
3. Once you have your desired airflow, leave the controls; after around ten seconds the flashing buttons will illuminate constantly to confirm the airflow is stored.

The set airflow will now be maintained throughout the life of the filters. When the extraction unit can no longer maintain the set airflow an alarm will be given and the display will indicate which filter should be changed.

1)



2)



3)



6. Maintenance

Maintenance UK

It is a legal requirement, under regulation 9 of the COSHH regulations that all local exhaust ventilation systems are thoroughly examined and tested at least once every 14 months (typically carried out annually). The approved code of practice recommends that a visual check should be carried out at least once a week.

COSHH requires the annual inspection and testing to be carried out by a competent person and specifies that documentation results are recorded in a log.

Contact the seller for more information about inspection and certification.

Maintenance General

User maintenance is limited to cleaning the unit and filter replacement, only the manufacturers trained maintenance technicians are authorised to carry out component testing and replacement. Unauthorised work or the use of unauthorised replacement filters may result in a potentially dangerous situation and/or damage to the extractor unit and will invalidate the manufacturer's warranty.


6.1 Cleaning the Unit

The stainless steel units should be cleaned with a proprietary stainless steel cleaner, in accordance with the manufacturer's user instructions.

The cooling inlets and outlets should be cleaned once a year to prevent build-up of dust and overheating of the unit.

6.2 Replacing Filters

The iQ system constantly monitors the condition of the individual filters. As the filters block the LCD display will show the relevant filter symbol filling up. (see section 1 for LCD details). Each filter symbol fills up in 5% increments, when the filter icon is filled, that particular filter will need replacing.



A log of the changes should be maintained by the user. The filters require attention when the display shows the filter blocked icon/ filter output signal (if fitted) or when the extractor no longer removes fume efficiently.

It is recommended that a spare set of filters are kept on site to avoid prolonged unit unavailability. Part numbers for replacement filters can be found on the filters fitted in your system.

To prevent overheating, units should not be run with a blocked filter condition, or with dust obstruction of Inlets / Outlets.

6.3 75% Filter Blocked Indication

When the filters become 75% blocked the buttons on the front of the extraction unit will turn from Green to flashing Green and if fitted the iQ system will output a signal to indicate this. At this time it is recommended spare filters are available as a change may be needed shortly.

6.4 Pre-Filter Replacement

Refer to section 2.2 for PPE requirements.

The Pre filter needs replacing when the display flashes like shown in the image below. At this point the buttons will flash Orange, a buzzer alarm will sound, the filter blocked signal will be given and is reset by following the pre filter replacement procedure as below.



To remove and replace the Pre filter follow the procedure detailed below.

1. Isolate the electrical supply to the extractor.
2. Undo the catches on the front of the unit and open the door.
3. The Pre filter is the lower of the two filters (refer to section 1 for filter location) using the handle on the front of the filter, pull it out of the unit.
4. Once removed you must make sure that the used filters are bagged and sealed.
5. Slide the new filter into position making sure it is pushed all the way in and is located correctly on the spigot in the back of the unit.
6. Close the door and fasten the two latches.

6.5 Combined Filter Replacement

The Combined filter needs replacing when the display flashes like shown in the image below. At this point the buttons will flash Orange, a buzzer alarm will sound, the filter blocked signal will be given and is reset by following the Combined filter replacement procedure as below.



To remove and replace the Combined filter follow the procedure detailed below.

1. Isolate the electrical supply to the extractor.
2. Undo the catches on the front of the unit and open the door.
3. The Combined filter is the higher of the two filters (refer to section 1 for filter location) rotate the lever below the filter through 180° to lower the combined filter.
4. Using the handle on the front of the filter, pull it out of the unit being careful to support it as it comes free as it is heavy.
5. Once removed you must make sure that the used filters are bagged and sealed.
6. Slide the new filter into position making sure it is pushed in all the way.
7. Rotate the lever back through 180° to raise the filter into position.
8. Close the door and fasten the two latches.
9. Reconnect the power supply.




The extractor should not run without filters fitted, if the combined filter is not installed correctly the iQ system will not allow the motor to operate.

7. iQ System Display Features/ Visual Alarms

7.1 iQ System Display Features

The iQ display has the ability to display all the faults associated with your extraction unit. The image below shows an example of some of the fault icons that may appear in the alarm window of the LCD display.



7.2 Visual Alarms on the iQ system

The iQ system can visually display a wide range of alarms on its LCD panel. The visual displays, meanings and solutions are detailed below. All alarms will trigger the system alarm interface output signal.

Over Temperature Alarm

If the iQ system detects an internal temperature greater than 60°C then it will automatically shut down the extractor to prevent damage to components within the extractor. To signal this fault the screen will have the image below, and the buttons will flash orange. As well as the visual alarm an acoustic alarm will sound and is reset by following the pre filter replacement procedure as below.



To restart the extractor once it has cooled down after an over temperature alarm, the unit needs to be placed in Standby mode then powered on again.

Hose blocked alarm

The iQ system features a 2 stage Hose blocked alarm.

- Partial hose blockage
- Full hose blockage

Partial hose blocked alarm

This alarm will become active when the iQ system detects a part blockage in the installation. The iQ system interprets a partial blockage as a vacuum spike within the ductwork but is only a partial blockage as the extractor is still able to maintain its set airflow.

During this time it is normal to hear the motor increase in speed. The blockage will need to remain in the ductwork for over 5 seconds before the alarm is given.

To signal this fault the screen will have the image below, and the buttons will flash orange. As well as the visual alarm an acoustic alarm will sound and is reset by clearing the blockage in the pipework. To remove the blockage, isolate the extraction unit from the mains, remove the flexible hose, locate and remove the blockage then reattach the hose as previously installed.



Full hose blockage

This alarm will become active when the iQ system detects a full blockage in the installation. The iQ system interprets a full blockage as a vacuum spike within the ductwork and is considered a full blocked as the extractor cannot maintain the set airflow with the blockage present.

During this time it is normal to hear the motor increase in speed. The blockage will need to remain in the ductwork for over 5 seconds before the alarm is given. To signal this fault the screen will have the image below, and the buttons will flash orange. As well as the visual alarm an acoustic alarm will sound and is reset by clearing the blockage in the pipework.

To remove the blockage, isolate the extraction unit from the mains, remove the flexible hose, locate and remove the blockage then reattach the hose as previously installed.



3. Locate the circular cut out in the shelf, at the front of the unit. *Refer to section 1.1.*
4. Inside the cut out there is a small button that can now be pressed back in.
5. Re-fit the Combined Filter, close the front door and re connect the mains supply.

To signal this fault the screen will have the image below, and the buttons will flash orange. As well as the visual alarm an acoustic alarm will sound and is reset by following the above procedure.



Heat Detection Shut off

The Oracle iQ system has an internally mounted thermal trip. That detects the temperature in the filter compartment. If the temperature rises above 55°C then the extraction unit will automatically shut down the motor and display the symbol below.


If this symbol is displayed the unit should be isolated from the mains supply and the unit should be fully inspected for evidence of the temperature rise. (Including inside the Pre filter).

Once the unit is safe to turn back on and the internal temperature has dropped below 50°C the thermal trip can be reset. To do this follow the procedure below.

1. Isolate the supply from the extractor.
2. Open the front door & remove the Combined Filter.

Filter status indicator 75% (Pre warning)

The 75% warning indicates that the filter is partially blocked and will shortly need to be replaced. The representative filter status 'box' on the display will confirm which filter will need replacing. All the display lights will start to flash green to indicate the filters are 75% full to enable stocks to be checked and schedule maintenance.



Combined filter not fitted

When the combined filter is not fitted or has been fitted incorrectly the screen will show. To signal this fault the screen will have the image below, and the buttons will flash orange. As well as the visual alarm an acoustic alarm will sound. This alarm is reset by correctly fitting the combined filter and securing in place using the filter lever.



Motor failure

The Oracle iQ system will monitor the motor status, if for any reason the motor stops working the fan icon below will be static and will flash the airflow will show zero and all the buttons will flash orange. As well as the visual alarm an acoustic alarm will sound, if this alarm sounds isolate the power to the unit to stop the alarm and contact the BOFA technical department (information can be found in section 2.01 of this manual).



7.3 USB Connectivity / USB Upload

The iQ system is equipped with a USB drive, which operates as a two-way device, as detailed below.

- Duplicating iQ settings
- Download iQ Data

Duplicating iQ settings (USB Upload)

This USB upload feature has been designed for customers that have multiple extractors and specific set of parameters that they wish to duplicate across their iQ extraction units. The procedure for duplicating extractor settings is detailed below.

1. Obtain the memory stick file from the seller (if specification has been pre-arranged with the seller) Or download original settings from your master iQ unit) (**Max capacity USB Stick 8GB**).
2. Download this file to a blank memory stick.
3. Place the iQ system in standby mode (Front power button glowing red).
4. Open the front door and insert the memory stick into the USB slot.
5. The LCD display will show "upload" press the button corresponding to this.
6. The display will show a progress complete bar and when finished a completion "Tick".
7. The USB stick can now be removed from the unit, the door closed and the extractor turned back On.



If the USB upload procedure fails the screen will display the symbol shown adjacent.



7.4 Download iQ Data (USB Download)

With this feature the customer is able to download all stored data within the iQ system, this information can then be used to keep records of how your iQ system is performing, this is also very beneficial for the technical team when diagnosing issues with the extraction system. The following list shows the information available within the event log.



Downloading iQ Data

To download the information from the iQ system please follow the procedure below.

1. Obtain a memory stick (**Max capacity USB Stick 8GB**).
2. Place the iQ system in standby mode (Front power button glowing red).
3. Open the front door and insert the memory stick into the USB slot.
4. The LCD display will show "download" press the button corresponding to this.
5. The display will show a progress complete bar and when finished a completion "Tick".
6. The USB stick can now be removed from the unit, the door closed and the extractor turned back On.



If the USB upload procedure fails the screen will display the symbol shown adjacent.



7.5 Information Collected by USB

The iQ system will take a snapshot of the system performance every 15 minutes or if a system adjustment is made or an alarm is triggered.

Some of the information captured is listed below:

- **Date**
- **Time**
- **Airflow**
- **Airflow Set point**
- **Pre filter % blocked**
- **Combined filter % blocked**
- **Inlet % (installation restriction)**
- **Motor output**
- **Internal Temperature**
- **Hours run**
- **Alarms**
- **Faults**

Date & Time

The date and time will be set as part of the testing stage with the manufacturer and set to GMT.

Airflow

This column shows the real time airflow through the extractor.

Airflow set point

Shows the target airflow that has been set by the user, this will record every time an adjustment is made.

Pre filter % blocked

The display on the extractor will show the pre filter blocking in 5% increments, but with this downloadable file the pre filter blockage is shown as an exact percentage of its full capacity.

Combined filter % blockage

The display on the extractor will show the combined filter blocking in 5% increments, but with this downloadable file the combined filter blockage is shown as an exact percentage of its full capacity.

Inlet % (installation restriction)

Shows the percentage of the iQ system capacity that is taken up by the installation (pipe work) this value would also rise if the inlet or pipe work becomes blocked.

Motor output

Shows the percentage the motor is being run at to achieve the airflow set by the user. This value will increase as the filters begin to block.

Internal temperature

Shows the internal temperature of the extraction unit, the sensor is mounted to the main PCB when this sensor reaches 60°C it will shut down the extractor and a log will be recorded.

Hours Run

This is a simple hours run counter that will begin from the first time the extraction is switched on by the user. The hours run counter will only be activated when the motor is running.

Alarms

When the iQ system has an issue that requires the user to act upon this is classed as an alarm, when this occurs a code will appear in this column, the main alarm codes are listed below.

Code	Meaning
16	Over temperature
32	Inlet partially blocked
64	Inlet fully blocked
128	No combined filter fitted
512	Motor failure
2048	System 100% blocked
4096	Combined filter blocked
8192	Pre filter blocked
524288	System 75% blocked

Faults

This column will display a code if a fault with the iQ system is detected, for analysis of any faults in this column please contact the BOFA helpline.

8. Troubleshooting


8.1 Fault Indication/Error Codes

The iQ system intelligently monitors the whole extraction unit. In the unlikely event of a problem with the extraction unit please read this section of the manual before contacting the helpline.

This section contains details on all faults the iQ system is able to display, these faults are detailed below.

Motor Failure

If the extraction unit develops a fault relating to the motor, then the motor icon on the display will flash, stop rotating and the airflow will read 0 m³/h.



If the above symbol is displayed power should be isolated from the extractor and arrangements should be made to replace the motor.

Internal Power Supply


The extractor is fitted with an internal transformer that outputs 12V DC providing the iQ system with power.

If the buttons on the front panel are not illuminated or operational this would indicate a problem with the internal power supply (provided the main isolation switch is in the ON position and voltage is proven at this point).

If the internal power supply has failed then, arrangements should be made to replace the transformer.

Error Codes on the iQ display

The iQ system is able to self-diagnose problems relating directly to the monitoring system. Faults are displayed as a number in the error window within the display.



In the event of an error code being displayed please contact your local representative or BOFA who will be able to diagnose the fault and advise on the most efficient solution.

USB diagnosis

For a "Real time" event log of any faults with your iQ system please see section 7.04 & 7.05 to download a full analysis of the extraction system.

9. Replacement Parts

9.1 Consumable Spares

The iQ extraction system contains a pre filter and a combined filter. These should be replaced when instructed to do so by the iQ system (see section 6 for replacing the filters).

To maintain performance it is important that the filters are replaced with identical BOFA filters. To re-order, please refer to the Filter number printed on the filter installed in your extraction unit. See part numbers below:

- 1UA1030160
- 1UA1030155

As this extractor is not supplied with power cord included, if you require one, please use the part numbers below:

- 1UA1070572 – UK power cord
- 1UA1070573 – EU power cord

9.2 Maintenance Protocol

The iQ data logging function enables the retrieval of filter change intervals. Users may also wish to record changes on the table below.

Unit Serial Number:			
Pre filter (1UA1030160)		Combined filter (1UA1030155)	
Date	Engineer	Date	Engineer

9.3 Filter Disposal

The Pre and Combined filters are manufactured from non-toxic materials. Filters are not re-usable, cleaning used filters is not permitted. The method of disposal of the used filters depends on the material deposited on them.

For your guidance

Deposit	EWC Listing*	Comment
Non Hazardous	15 02 03	Can be disposed of as non-hazardous waste.
Hazardous	15 02 02M	The type of hazard needs to be identified and the associated risks defined. The thresholds for these risks can then be compared with the amount of material in the filters to see if they fall into the hazardous category, if so, the filters will need to be disposed of in line with the local/national regulations.

*European Waste Catalogue

9.4 Unit Disposal

This product contains materials that can be recycled and reused. Distributors within Europe must comply with the WEEE regulations 2012/19/EU. Please contact your distributor for information regarding end of life disposal.

(For Customers in outside the EU and UK)

Dispose of in accordance to local state, provincial, municipal or federal regulations.

10. System Specifications

10.1 Oracle iQ W3 Specifications/Spares

Minimum flowrate: 100m³/h (58.9cfm)
Maximum flowrate: 370m³/h (217.8cfm)
Airflow measurement method: Windvane
Suction pressure: 96mbar +/- 3%
Weight: 68.5Kg (151lbs)
Motor: Centrifugal Fan
Output: 1100w
Electrical supply: 115-230V
Hertz: 50/60Hz
Full Load Current: 12.5A
No of phases: 1
Noise Level: Below 80dB (A) (at operator position)
Maximum Altitude – 2000M

Size:

	Metric (mm)	Imperial (inches)
Height	975	38.4
Width	450	17.7
Depth	525	20.7

Filters:

Filter Type	Surface area	Efficiency
Pre filter	12.0m ²	F8 - ePM1 70%
Combined filter	3.0m ²	99.995% @ 0.3micron

Combined Filter (Gas section)

Filter Type	Carbon type	Volume
Combined filter (Gas)	Activated carbon	18.77 ltrs

Environmental operating range:

Temperature: +5°C to + 30°C

Humidity: Max 80% RH up to 31°C
Max 50% RH at 40°C

Process fume/gas entering this system should be within the above temperature range.

Wiring schematic available upon request

Spares parts list available upon request

Contact Information

BOFA Headquarters

19-20 Balena Close
Creekmoor industrial Estate
Poole
Dorset
BH17 7DU
UK

Tel. +44 (0) 1202 699 444

Email. GRPBOFASales@Donaldson.com

Donaldson Filtration Deutschland GmbH

Büssingstrasse 1
42781 Haan
Deutschland
Germany
DE121399181

Tel. +49 (0) 40 739 3735-15

Email. vertrieb@bofa.co.uk

BOFA Americas, Inc

303 S.Madison Street
Staunton
Illinois
62088
USA

Tel. +1 (618) 205 5007

Email. sales@bofaamericas.com



Local Exhaust Ventilation System - **Inspection Record**

Health & Safety at Work Act 1974 - Control of Substances Hazardous to Health - Regulation 9 (2002)
Thorough Examination and Testing of Local Exhaust Ventilation Systems

Company:	System Designation:	System Installation Date:
Designated Person:		

Inspection and Maintenance Schedules

1. Daily checks
2. Weekly inspection of process enclosure, extract offtake, hose/ducting and extract/filtration unit.
3. Monthly inspection of process enclosure, extract offtake, hose/ducting and extract/filtration unit.
4. Yearly inspection / testing

**Process enclosure, extract offtake(s), hose/ducting and extract/filtration unit.
Inspection and Maintenance Record**

1. Daily inspection

Inspection of the process to ensure extract devices/nozzles/enclosures/hoses are in place and correctly positioned. Examination of the extractor to ensure it is running. This to be carried out by the operator. Daily inspection not recorded.

2. Weekly Inspection

Weekly inspection by supervisor of physical condition of extract devices/nozzles/enclosures/hoses and extraction unit for damage, change (parts added or removed) and correct operation etc. Check also that daily inspections have been completed. Tick boxes to confirm system ok / change. Add details of any changes. Report changes to Engineering Manager. Record any remedial actions taken.

Week number	Date	System ok	System Change	Details of change / repairs etc	Initial
1					
2					
3					
4					
5					
6					
7					
8					
9					
10					
11					
12					
13					
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					

**Process enclosure, extract offtake, hose/ducting and extract/filtration unit.
Inspection and Maintenance Record**

2. Weekly Inspection

. . . . Continued

Weekly inspection by supervisor of physical condition of extract devices/nozzles/enclosures/hoses and extraction unit for damage, change (parts added or removed) and correct operation etc. Check also that daily inspections have been completed. Tick boxes to confirm system ok / change. Add details of any changes. Report changes to Engineering Manager. Record any remedial actions taken.					
Week number	Date	System ok	System Change	Details of change / repairs etc	Initial
27					
28					
29					
30					
31					
32					
33					
34					
35					
36					
37					
38					
39					
40					
41					
42					
43					
44					
45					
46					
47					
48					
49					
50					
51					
52					

Process enclosure, extract offtake, hose/ducting and extract/filtration unit. Inspection and Maintenance Record

3. Monthly Inspection

<p>In addition to weekly checks. Disconnect hoses and check for blockage and smooth operation of fan, signs of dust or vapour / gas / odour carry over. Tick boxes to confirm system ok / change. Add details of any changes. Report changes to Engineering Manager. Record any remedial actions taken.</p>					
Month number	Date	System ok	System Change	Details of change / repairs etc	Initial
1					
2					
3					
4					
5					
6					
7					
8					
9					
10					
11					
12					

4. Yearly Inspection

<p>Annual service To include all regular checks together with inspection of filter condition and replacement where necessary, motor and electrical checks,</p>	<p>Comments</p>	<p>Signature of Supervisor :</p> <p>Date:</p>
<p>Annual Thorough Inspection and Testing of LEV System in accordance with C.O.S.H.H. Regulation 9 (max interval 14 months) including reporting.</p>	<p>Comments</p>	<p>Signature of Supervisor :</p> <p>Date:</p>