

DustPRO 1000 iQ

Fume Extraction System - DustPRO Range

Datasheet

Technical Specification and Product Information

A system for medium to heavy-duty industrial applications.

The DustPRO 1000 iQ extraction system is ideal for medium to heavy-duty applications that generate large amounts of particulate. With a greater airflow than the DustPRO 500 iQ, it also offers significant filter capacity.

FEATURES


- Long-life, low-cost replacement filters
- High contrast display

Remote diagnostics via




Approvals: UKCA and CE | cUL | UL*

TECHNICAL SPECIFICATION



- iQ display
- On/off switch 2.
- 3. Power cable
- Signal/interface cable



- Door hinges
- Hose inlet connection 4.92" (125 mm) 10. Castors
- Blower cooling inlet 7.
- Air outlet/blower cooling outlet
- 币
 - Door latches

 - 11. USB port

TECHNICAL DATA

Voltage	Unrestricted airflow** (+/- 10%)		Settable airflow range***		Pressure (+/- 10%)	Dimensions (H x W x D)		Weight (+/- 5%)		Noise level****	Frequency	Full load current
V	cfm	m³/hr	cfm	m³/hr	mbar	in	mm	lbs	kg	dB(A)	Hz	amps
115	500	005	470 440	200 750	00	47.4 04.0 04.0	1205 020 040	200	0.5	. 05	F0/00	19.5
230	520	885	176-442 300-750	60	47.4 x 24.2 x 31.9	1205 x 620 x 810	209	95	< 85	50/60	12.8	

AIRFLOW

Pre-filter



HEPA filter




Clean filtered air



Contaminated air



Particulate



PART NUMBERS - SYSTEM

Description	Part number		
Powder-coated, 230 V UK plug	1U30811619-A-2181-UK		
Powder-coated, 230 V EU plug	1U30811619-A-2181-EU		
Powder-coated, 230 V 24 V S/S, SOK, O/R, UK plug	1U6530811619-A-2181-UK		
Powder-coated, 230 V 24 V S/S, SOK, O/R, EU plug	1U6530811619-A-2181-EU		
Powder-coated, 230 V 24 V S/S, SOK, O/R, USA plug	1U6530811619-A-2181-US		

FILTER SPECIFICATIONS

Model	Surface m (app	Filter		
	ft²	m²	efficiency	
Pre-filter bag	44.1	4.1	95% @ 0.9 microns	
HEPA filter	80.7	7.5	99.995% @ 0.3 microns	

PART NUMBERS - FILTERS

Pre-filter bag	HEPA filter
1UA1030395	1UA1030394

CUSTOMIZATIONS

Options	Power cables
Power cables Remote stop/start signal (S/S) System OK signal (SOK) Override (O/R) Exhaust box	Type B Type E Type G
Cabinet construction	
Powder-coated mild steel (RAL7016)	

*cUL | UL: Tested to the appropriate standards, but testing may be provided by alternate nationally recognized test laboratories. Certain product configurations may affect the certification. Please speak to your sales representative.

Datasheet correct at time of publishing. Where applicable, the carbon used in Donaldson BOFA systems is capable of removing a wide range of VOCs, however it is the responsibility of the user to ensure the carbon is suitable for their application. For specific applications, please contact us for details.

Many factors beyond the control of Donaldson can affect the use and performance of Donaldson products in a particular application, including the conditions under which the product is used. Since these factors are uniquely within the user's knowledge and control, it is essential the user evaluate the products to determine whether the product is fit for the particular purpose and suitable for the user's application. All products, product specifications, availability and data are subject to change without notice, and may vary by region or country.



Approvals: REACH and RoHS. See invididual product technical data for specific accreditations



Donaldson BOFA

Tel. +44 (0) 1202 699 444 Email. bofasales@donaldson.com Web. donaldsonbofa.com

Germany Email. bofavertrieb@donaldson.com USA

Tel. +1 (618) 205 5007 Email. bofasalesus@donaldson.com

^{**} Unrestricted airflow: The airflow values provided with clean filters, no hose kit, at 230 V, measured by using a wind vane. The numbers may vary depending on voltage and test procedure used.

^{***} Settable range: Donaldson BOFA recommends utilizing the lowest flow rate that achieves the correct capture velocity for your application in order to maximize filter life.

^{****} Noise level: At typical operating speed.