

Datasheet

Technical Specification and Product Information

A system for heavy-duty printing applications.

The PrintPRO Oracle DS fume extraction system is designed to filter fumes generated from dye sublimation printers. With a large filter capacity and high airflow, it's an ideal choice for heavy-duty applications that produce large amounts of particulate and gaseous organic compounds.


FEATURES

- Long-life, low-cost replacement filters
- High airflow rates
- Automatic fluid drain

Approvals: UKCA and CE



TECHNICAL SPECIFICATION





1. Control panel
2. On/off switch
3. Power cable
4. Signal/interface cable
5. Door hinges
6. Hose inlet connection - 2.0/2.9" (50/75mm)
7. Exhaust outlet
8. Blower cooling inlet
9. Door latches
10. Castors
11. Drain valve

TECHNICAL DATA

Voltage	Airflow		Pressure (+/- 10%)	Dimensions (H x W x D)		Weight (+/- 5%)		Noise level*	Frequency	Full load current
V	cfm	m ³ /hr	mbar	in	mm	lbs	kg	dB(A)	Hz	amps
115-230	223	380	96	37.6 x 17.0 x 18.7	955 x 430 x 475	143	65	< 60	50/60	12.5

AIRFLOW



FILTER SPECIFICATIONS

Model	Surface media area (approx)		Filter efficiency
	ft ²	m ²	
Hydrophobic HEPA filter	80.7	7.5	99.995% @ 0.3 microns

Model	Foam media
Sponge coalescent filter	58 grade open cell foam

Model	Activated carbon volume	
	ltr	
Gas filter	22.0	

PART NUMBERS - FILTERS

Sponge filter	HEPA filter	Activated carbon filter
1UA1030387		
1UA1030219 (twin pack)	1UA1030220	1UA1030247

Datasheet correct at time of publishing. Where applicable, the carbon used in Donaldson BOFA systems is capable of removing a wide range of VOCs, however it is the responsibility of the user to ensure the carbon is suitable for their application. For specific applications, please contact us for details.

Important Notice

Many factors beyond the control of Donaldson can affect the use and performance of Donaldson products in a particular application, including the conditions under which the product is used. Since these factors are uniquely within the user's knowledge and control, it is essential the user evaluate the products to determine whether the product is fit for the particular purpose and suitable for the user's application. All products, product specifications, availability and data are subject to change without notice, and may vary by region or country.

* Noise level: At typical operating speed.



Approvals: REACH and RoHS. See individual product technical data for specific accreditations.

Donaldson
BOFA

Donaldson BOFA

UK & ROW
Tel. +44 (0) 1202 699 444
Email. bofasales@donaldson.com
Web. donaldsonbofa.com

Germany
Email. bofavertrieb@donaldson.com

USA
Tel. +1 (618) 205 5007
Email. bofasalesus@donaldson.com

ENG (December 2025) Donaldson BOFA PrintPRO Oracle DS Datasheet. ©2011-2025 Donaldson Company, Inc. Donaldson, Torit, Dalmatic, Delta P, Delta P Plus, Downflow, Dura-Life, Easy Duct, PowerCore, Synteq XP, Ultra-Web, Unimaster and the color blue are marks of Donaldson Company, Inc. All other marks belong to their respective owners.